

MY CUBE®

OPERATING MANUAL

WELCOME

Thank you for purchasing a MyCube safe.

MyCube keeps your valuables secure and organized so you are free from worry. We know owning one will give you greater peace of mind.

As two women running MyCube, we took extra care to consider design, quality, and convenience - the same qualities that inform our daily lives.

With a customer service team that is available around the clock, we are here for you.

Thanks for choosing MyCube.

Lois and Joyce

IN THE BOX

MyKit Box Contents



1 Allen Wrench



8 Screws



8 Washers



4 AA Batteries




2 Manual Keys

FOLLOW THESE STEPS

Step 1


To open door, pull felt strips.



FOLLOW THESE STEPS

Step 2


To power safe, remove battery cap from back of door and insert 4 AA batteries.



FOLLOW THESE STEPS

Step 3


To set your user code, press CLEAR 2x, "PROG" will appear on the screen. Press 68 LOCK, "NEU" will appear on the screen. Press your 4 digit code, and press LOCK. Your code is now set.



FOLLOW THESE STEPS

Step 4


To open the safe enter your 4 digit code. To lock the safe simply press LOCK.



FOLLOW THESE STEPS

Step 5

When batteries run out, remove the black plate with the MyCube logo from the keypad. Insert key in exposed hole. Turn key to open door. Insert batteries as in Step 2.



Key Hole


FOLLOW THESE STEPS

Step 6

To change your user code, press CLEAR 2x, "PROG" will appear on the screen. Press 68 LOCK, "NEU" will appear on the screen. Press your 4 digit code, and press LOCK. Your new code is now set.

Press Clear

Two Times



IMPORTANT NOTE

Keep your keys out of the safe and register your key number on mycubesafe.com

This is the only way to replace your keys should you misplace them. **MyCube strongly recommends changing your batteries every year.**

INSTALLATION

There are eight (8) points of contact to secure your MyCube. Four (4) points on the bottom, and four (4) points on the back of each safe. When the safe is in the desired position, take a marker and through the pre-drilled holes inside the safe, mark the surface(s) on which you will be securing the screws.

Remove the safe and use a power drill and drill into each mark to make holes for the provided screws. Put the safe back in position, and line up each hole in the safe over each of the drilled points. Place each of the provided washers over each hole inside the safe, and with a screwdriver or right-angle power drill, secure each screw into the surface.

CONTACT US

Visit mycubesafe.com for product demonstration videos, installation and product manuals.

Questions, call Customer Service

(800) 590-1592

For support, email info@mycubesafe.com

Find us on social media @mycubesafe

